



Protective window films, edge retention systems - *a gem of a solution*

0845 602 7782

enquiries@dymondproducts.com

DYMOND AUTOMOTIVE Solar Performance Specifications

NON-REFLECTIVE TINTED SERIES QUICK DRY PLUS 2PLY- Solar Performance Specifications														
	Solar Energy			Visible Light				UVR	SC	SHR	TSER	GR	E	U-VALUE
	T	A	R	T	A	R								
QUICK DRY PLUS 2PLY RANGE						Int.	Ext.							
NR CHARCOAL 05 2PLY	41	54	5	4	92	4	3	99	.66	34	43	96	.89	1.12
NR CHARCOAL 20 2PLY	48	47	5	19	77	4	3	99	.71	29	39	79	.89	1.12
NR CHARCOAL 30 2PLY	54	40	6	30	66	4	4	99	.76	24	35	67	.89	1.12
NR CHARCOAL 40 2PLY	56	39	5	39	57	4	4	99	.76	24	33	57	.89	1.12
NR CHARCOAL 50 2PLY	60	35	5	48	48	4	4	99	.81	19	30	47	.89	1.12
NON-REFLECTIVE TINTED SERIES QUICK DRY 1PLY - Solar Performance Specifications														
QUICK DRY 1PLY RANGE														
NR CHARCOAL 05 1PLY	45	48	7	6	87	7	6	99	.67	33	40	93	.85	1.12
NR CHARCOAL 20 1PLY	48	46	6	21	73	6	6	99	.71	29	39	77	.86	1.15
NR CHARCOAL 40 1PLY	55	39	6	38	55	7	7	99	.76	24	34	58	.86	1.14
NR CHARCOAL 50 1PLY	60	33	7	51	43	6	7	99	.80	18	31	44	.86	1.14
NR CHARCOAL 70 1PLY	70	21	9	70	24	6	7	99	.88	13	24	20	.86	1.13

DYMOND AUTOMOTIVE Construction and Availability Specifications

NON-REFLECTIVE TINTED SERIES – Construction and Availability									
	110' ROLLS			ADHESIVE			SRC	Mil	Ply
QUICK DRY PLUS 2PLY RANGE									
NR CHARCOAL 05	60"	40"	20"			PS	Yes	1.5	2
NR CHARCOAL 20	60"	40"	20"			PS	Yes	1.5	2
NR CHARCOAL 30	60"	40"	20"			PS	Yes	1.5	2
NR CHARCOAL 40	60"	40"	20"			PS	Yes	1.5	2
NR CHARCOAL 50	60"	40"	20"			PS	Yes	1.5	2
NON-REFLECTIVE TINTED SERIES QUICK DRY 1PLY - Solar Performance Specifications									
QUICK DRY 1PLY RANGE		100'							
NR CHARCOAL 05	60"	30"				PS	Yes	1	1
NR CHARCOAL 20	60"	30"				PS	Yes	1	1
NR CHARCOAL 40 (35)	60"	30"				PS	Yes	1	1
NR CHARCOAL 50	60"	30"				PS	Yes	1	1
NR CHARCOAL 70	60"	30"				PS	Yes	1	1