

REFLECTIVE SERIES - SOLAR PERFORMANCE SPECIFICATIONS – INTERNAL FILM RANGE

	Solar Energy			Visible Light				UVR	SC	SHGC	SHR	TSER	GR
	TR	AB	RF	TR	AB	RF							
						Int.	Ext.						
DRF SV 05 PS = R SILVER 05	4	18	78	5	13	82	82	99	.10	.09	87	91	96
DRF SV 20 PS = R SILVER 20	13	34	53	18	27	56	55	99	.25	.20	74	78	80
DRF SV 35 PS = R SILVER 35	28	35	37	41	30	28	29	99	.43	.38	51	63	60
DRF SV 50 PS = R SILVER 50	38	36	26	51	30	21	19	99	.56	.45	42	52	46
DRF BR 10 PS = R BRONZE 10	9	60	31	10	69	21	23	99	.31	.23	76	74	89
DRF BR 30 PS = R BRONZE 30	32	51	17	32	44	24	13	99	.53	.42	47	53	67
DRF GO 10 PS = R GOLD 15	12	44	44	14	40	46	49	99	.28	.25	78	76	84
DRF GR 05 PS = R GREY 05	8	66	26	5	85	57	10	99	.25	.20	75	78	94
DRF GR 10 PS = R GREY 10	9	64	57	8	72	18	19	99	.26	.22	73	76	92
DRF GR 20 PS = R GREY 20	25	52	23	22	69	22	9	99	.49	.25	51	58	76
DRF GR 35 PS = R GREY 35	42	49	9	36	56	9	8	99	.63	.38	37	46	60
DRF GN 10 PS = R GREEN 10	10	53	37	10	66	24	19	99	.27	.22	73	76	89
DRF BL 15 PS = R BLUE 15	16	47	37	11	51	38	32	99	.33	.27	67	76	88

REFLECTIVE SERIES - SOLAR PERFORMANCE SPECIFICATIONS – EXTERNAL FILM RANGE

DRF SV 15 PS XTE = RS15X-SRC*	12	20	68	15	20	62	65	99	.16	.14	81	88	85
DRF SV 30 PS XTE = RS30X-SRC*	29	25	46	36	23	41	41	99	.30	.31	69	74	68
DRF SV 20 PS XT = RS20X-SRC	14	23	63	19	16	65	59	99	.25	.16	75	78	82
DRF SV 35 PS XT = RS35X-SRC	29	34	39	38	23	39	37	99	.45	.36	55	61	58
DRF BR 10 PS XT = RBR10X-SRC	9	52	39	10	24	66	61	99	.24	.23	76	79	89
DRF GR 10 PS XT = RGR10X-SRC	9	51	59	8	71	21	23	99	.26	.18	74	76	93

HIGH PERFORMANCE SERIES - SOLAR PERFORMANCE SPECIFICATIONS – INTERNAL FILM RANGE

DHP NT 20 PS = HP NATURAL 20	24	63	13	21	72	7	7	99	.49	.37	51	58	77
DHP NT 35 PS = HP NATURAL 35	36	48	18	39	47	14	14	99	.57	.45	43	51	57
DHP NT 50 PS = HP NATURAL 50	53	39	8	53	39	8	8	99	.74	.66	26	36	42
DHP CH 05 PS = HP CHARCOAL 05	20	68	12	5	90	5	5	99	.46	.36	54	61	94
DHP CH 15 PS = HP CHARCOAL 15	29	63	8	14	78	8	8	99	.54	.44	46	53	89
DHP CH 35 PS = HP CHARCOAL 35	45	48	7	39	53	8	8	99	.68	.52	32	41	57
DHP CH 50 PS = HP CHARCOAL 50	54	39	7	54	38	8	8	99	.75	.67	25	35	41

HIGH PERFORMANCE SERIES - SOLAR PERFORMANCE SPECIFICATIONS – EXTERNAL FILM RANGE

DHP NT 20 PS XT = HP NAT 20 X-SRC	15	59	26	20	60	20	20	99	.30	.30	67	73	81
DHP NT 35 PS XT = HP NAT 35 X-SRC	25	52	23	35	47	18	20	99	.40	.38	59	65	65

ESTATE SOLAR SERIES – SOLAR PERFORMANCE SPECIFICATIONS

	Solar Energy			Visible Light				UVR	SC	SHGC	SHR	TSER	GR
	TR	AB	RF	TR	AB	RF							
						Int.	Ext.						
DES NE 20 PS = NEUTRAL 20	20	51	29	21	48	31	32	99	.30	.32	65	68	78
DES NE 35 PS = NEUTRAL 35	29	49	22	34	44	22	22	99	.31	.34	59	66	63
DES SB 20 PS = SOLAR BRONZE 20	13	42	45	20	44	36	36	99	.20	.22	68	77	79
DES SB 20 PS = SOLAR BRONZE 35	25	36	39	35	39	26	26	99	.39	.34	59	65	63

ESTATE DUAL REFLECTIVE SERIES – SOLAR PERFORMANCE SPECIFICATIONS

DES DR 15 PS = DUAL REFLECT.15	10	38	52	13	62	25	50	99	.25	.21	76	80	88
DES DR 30 PS = DUAL REFLECT.30	23	45	32	29	37	34	37	99	.42	.34	58	64	68

NANO-TECHNOLOGY IR SOLAR SERIES – SOLAR PERFORMANCE SPECIFICATIONS

	TR	AB	RF	TR	AB	RF	RF	UVR	SC	SHGC	SHR	TSER	GR	% NIR
														BLOCK
DPL IR 70 PS = ICE COOL 70	46	49	5	69	24	7	7	99	.70	.45	82	56	24	
DPL IR NE 70 PS = ICE COOL NE 70	47	26	27	70	23	7	7	99	.58	.49	70	50	20	

ARCHITECTURAL CHARCOAL TINTED NON-REFLECTIVE SERIES – SOLAR PERFORMANCE SPECIFICATIONS

DNR CH 05 PS = NR CHARCOAL 05	45	48	7	6	88	6	6	99	.67	.61	33	40	93
DNR CH 20 PS = NR CHARCOAL 20	48	46	6	21	73	6	6	99	.71	.64	29	39	77
DNR CH 35 PS = NR CHARCOAL 35	55	39	6	38	56	6	6	99	.76	.65	24	34	58
DNR CH 50 PS = NR CHARCOAL 50	60	33	7	51	43	6	6	99	.80	.71	20	31	44
DNR CH 075 PS = NR CHARCOAL 70	70	21	9	70	22	8	8	99	.88	.78	12	24	12

ARCHITECTURAL COLOUR TINTED NON-REFLECTIVE SERIES – SOLAR PERFORMANCE SPECIFICATIONS

DNR GR 05 PS = NR GREY 05	41	53	6	4	90	6	6	99	.59	.64	36	44	96
DNR GR 20 PS = NR GREY 20	49	45	6	22	73	5	5	99	.64	.72	28	38	76
DNR GR 50 PS = NR GREY 50	60	33	7	51	43	6	6	99	.71	.80	20	31	44
DNR GN 35 PS = NR GREEN 35	56	37	7	32	61	7	6	99	.65	.77	23	33	64
DNR BR 35 PS = NR BRONZE 35	48	45	7	30	64	6	6	99	.65	.71	29	39	67
DNR BL 35 PS = NR BLUE 35	55	38	7	38	55	7	6	99	.65	.76	24	34	58

Document No: FDR/1

T: 0845 602 7782 or 01480 450850

Date: 2018

E: sales@dymondproducts.com

www.dymondproducts.com

